



A Furukawa Company

Your Optical Fiber Solutions Partner®

OFS | www.ofsoptics.com

Item # P25561-BKRJ, Crimp & Cleave SC and SC-RJ Connectors

SC-RJ Connector for GiHCS® 50/200/230, 62.5/200/230 GiHCS® and 200/230 HCS®



[Specifications](#) | [Connector Performance Data](#) | [Cable Design](#) | [Compatibility](#) | [Ordering Information](#)

Specifications	
Color	Black
Connector Type	SC-RJ
For Use With Optical Fiber Cable Types	Graded-Index 50/200/230 and 62.5/200/230 GiHCS® and Step-Index HCS® 200/230 A-System® cables.

Connector Performance Data	
Typical Insertion Loss @ 850 nm	200/230 HCS® - 0.7 dB 50/200/230 GiHCS® - 1.0 dB 62.5/200/230 GiHCS® - 0.7 dB
Maximum Insertion Loss @ 850 nm	200/230 HCS® - 1.0 dB 50/200/230 GiHCS® - 1.5 dB 62.5/200/230 GiHCS® - 1.2 dB
Typical Insertion Loss @ 1300 nm	50/200/230 GiHCS® - 1.2 dB 62.5/200/230 GiHCS® - 0.9 dB
Maximum Insertion Loss @ 1300	50/200/230 GiHCS® - 1.7 dB

nm	62.5/200/230 GiHCS® - 1.4 dB
Operating Temperature	-40 to +85 °C
Cable Crimp Retention	22.5 lb 100 N
Overall Length	2.2 in 55 mm

Cable Design		—
Jacket Diameter	2.5 mm	

Compatibility		—
Compatible Termination Kit	DT03732-SC1	
Compatible Insertion Loss Test Kit	P10188-14	

Ordering Information		—
Order From Location	AVON LOCATION 1.888.438.9936 toll-free in the United States and Canada 1.860.678.0371 from outside the U.S.A. 55 Darling Drive Avon, CT 06001, USA	