
Specifications for Plastic Optical Fiber

<u>Multicore POF</u> [™] <u>MBI-2000</u>

- Issued on : April 30, 2020
- Issued by : Asahi Kasei Corporation Plastic Optical Fiber Marketing & Development Gr

1, STRUCTURE

| ITEM | UNIT | Specifications |
|----------------|------|---------------------|
| Core Material | | РММА |
| Clad Material | | Fluorinated Polymer |
| Fiber Diameter | μm | 2000 ± 120 |
| Core Number | | 7400 |
| NA | | 0.5 |



Fiber (Core & Clad)

2, PROPERTIES

| ITEM | UNIT | Specification | |
|---------------------------------|------|---------------|----|
| Application Temperature Range | °C | -55 ~ 60 | |
| Tensile Strength at Break Point | Ν | ≥ 140 | *] |

Sample conditions

| Temperature: | T = 23°C |
|---------------|----------|
| Humidity: | RH = 50% |
| Storage time: | t = 200h |

*1 : Interval between grippers = 100 mm, Tensile Speed = 100mm/min

3, RoHS certification

The product does not contain RoHS 2 hazardous substances, Cadmium, Lead, Mercury, Chromium (VI), PBB, PBDE, DIBP, DEHP, DBP and BBP intentionally.