## Specifications for Plastic Optical Fiber

# Multicore POF<sup>™</sup> MCI-750-10

Issued on: April 8, 2020

Issued by: Asahi Kasei Corporation


Plastic Optical Fiber

Marketing & Development Gr



### 1, STRUCTURE

ITEM	UNIT	Specifications
Core Material		PMMA
Clad Material		Fluorinated Polymer
Core reflective index		1.49
Reflective index Profile		Step index
Fiber Diameter	μm	750 ± 45
Core Number		7400
NA		0.5
Jacket Material		PE
Jacket Diameter	μm	1000 ± 60
Jacket Color		Black
Approx. weight	g/m	0.8





#### 2, PROPERTIES

ITEM	UNIT	Specifications	
Storage Temperature Range	°C	-55 ~ 60	
Application Temperature Range	°C	-55 ~ 60	
Tensile Strength at Break Point	N	≥ 45	*1

#### Sample conditions

Temperature:  $T = 23^{\circ}C$ Humidity: RH = 50%Storage time: t = 200h

### 3, RoHS certification

The product does not contain RoHS 2 hazardous substances, Cadmium, Lead, Mercury, Chromium (VI), PBB, PBDE, DIBP, DEHP, DBP and BBP intentionally.

<sup>\*1 :</sup> Interval between grippers = 100 mm, Tensile Speed = 100mm/min