

HCS® 200 µm All Silica Low OH Step-Index Optical Fiber

P/N: CF01493-51



Overview

Low OH concentration optimizes these fibers for use in the near-IR wavelengths. Biocompatibility features make these fibers ideal for laser surgery and other medical applications.

The all-silica base construction also creates a high damage threshold and high-performance optical properties.

High temperature environments require the use of PYROCOAT® polyimide coating.

Typical Applications

Aircraft/Industrial Cabling
Engine Controls
High-Power Laser Delivery
Laser Surgery
Laser Welding and Cutting
Near-IR Spectroscopy
Radiation Analysis
Sensing



HCS® 200 µm All Silica Low OH Step-Index Optical Fiber

P/N: CF01493-51

Product Description	200 All Silica Low OH Step-Index
Physical Characteristics	
Core Diameter	200 ± 5 μm
Cladding Diameter	240 ± 5 μm
Coating Diameter	260 ± 5 μm
Buffer Diameter	375 ± 30 μm
Core/Clad Offset	≤ 7 µm
Crimp & Cleave Compatible	No
Cladding Material	HCS fluoroacrylate
Buffer Material	ETFE
Standard Buffer Color	Natural
Optical Characteristics	
Туре	Multimode Step-Index
Numerical Aperture	0.22
Attenuation @ 850 nm	≤ 8 dB/km
Water Content	Low OH
Mechanical and Environmental	
Operating Temperature	-65 to +125 °C
Short-Term Bend Radius	≥ 9 mm
Long-Term Bend Radius	≥ 14 mm
Proof Test Level	≥ 200 kpsi (1.38 GPa)
Order by Part Number	CF01493-51
	HCL-M0200T

For additional information please contact your sales representative.

You can also visit our website at www.ofsoptics.com or call 1-888-fiberhelp (1-888-342-3743) USA or 1-770-798-5555 outside the USA.







OFS Marketing Communications

Date: 12/19

HCS and PYROCOAT are registered trademarks of OFS Fitel, LLC. OFS reserves the right to make changes to the prices and product(s) described in this document at any time without notice. This document is for informational purposes only and is not intended to modify or supplement any OFS warranties or specifications relating to any of its products or services.